

Toggle Switches

INDUSTRIAL



MODEL	DESCRIPTION
1TL1-1	SPDT ON-OFF-ON
1TL1-3	SPDT ON-ON
1TL1-7	SPDT (ON)-OFF-(ON)

() = Momentary

MINIATURE

CIRCUIT-TEST

Miniature toggle switch with solder terminals. Rated at 125VAC. Approximate sizes 12.5 x 7.9mm single pole, 12.5 x 12.5mm double pole.



MODEL	DESCRIPTION
451-301	SPST 6A, ON-OFF
451-301-10	SPST 6A, ON-OFF, Pkg/10
451-302	SPDT 6A, ON-ON
451-302-10	SPDT 6A, ON-ON, Pkg/10
451-303	SPDT 6A, ON-OFF-ON
451-405	DPDT 5A, ON-(ON)
451-410	DPDT 5A, ON-OFF-(ON)
451-415	DPDT 5A, (ON)-OFF-(ON)
451-305	DPDT 6A, ON-ON
451-305-10	DPDT 6A, ON-ON, Pkg/10
451-306	DPDT 6A, ON-OFF-ON
451-306-10	DPDT 6A, ON-OFF-ON, Pkg/10
451-420	4PDT 6A, ON-ON
451-425	4DPT 6A, ON-OFF-ON

() = Momentary

SUBMINIATURE

CIRCUIT-TEST

452-110



MODEL	DESCRIPTION
452-110	SPST 3A, ON-OFF
452-110-10	SPST 3A, ON-OFF, Pkg/10
452-115	SPDT 3A, ON-ON
452-115-10	SPDT 3A, ON-ON, Pkg/10
452-120	DPDT 3A, ON-ON
452-120-10	DPDT 3A, ON-ON, Pkg/10

ACCESSORIES



MODEL	DESCRIPTION
41-901-5	Switch Caps - Black, Pkg/5
41-902-5	Switch Caps - Red, Pkg/5
41-906-5	Switch Caps - Blue, Pkg/5
41-909-5	Switch Caps - White, Pkg/5
451-905	Weatherproof Boot (Mini toggle switch) - M6 x 0.75
451-906	Weatherproof Boot (Mini toggle switch) - 1/4-40

STANDARD


CIRCUIT-TEST

MODEL	DESCRIPTION
453-320	SPST 4A, ON-OFF, Solder terminals
453-320-10	SPST 4A, ON-OFF, Solder terminals, Pkg/10
453-326	SPDT 15A, ON-ON, Screw terminals
453-327	SPDT 15A, ON-OFF-ON, Screw terminals
453-321	DPDT 10A, ON-ON, Screw terminals
453-321-10	DPDT 10A, ON-ON, Screw terminals, Pkg/10
453-322	DPDT 10A, ON-OFF-ON, Screw terminals
453-322-10	DPDT 10A, ON-OFF-ON, Screw terminals, Pkg/10
453-329	DPDT 15A, ON-ON, Screw terminals
453-330	DPDT 15A, ON-OFF-ON, Screw terminals
453-410	DPDT 15A, ON-(ON), Screw terminals
453-420	DPDT 15A, (ON)-OFF-(ON), Screw terminals

() = Momentary



MODEL	DESCRIPTION
453-350	SPST 10A, ON-OFF, Solder Terminals
453-425	4PDT 25A, ON-OFF, Solder terminals
453-430	4PDT 25A, ON-OFF-ON, Solder terminals



MODEL	DESCRIPTION
30-1250	Toggle Switch Safety Guard
453-905	Weatherproof Boot (M12, P1 Thread)

Miniature Switches

CIRCUIT-TEST

Miniature pushbutton switch with solder terminals. Hole mounting size: 7mm (0.275"). Rated 1A /125V AC.



MODEL	DESCRIPTION
456-101	1A (ON)-OFF Black Cap
456-101-10	1A (ON)-OFF Black Cap, Pkg/10
456-102	1A (ON)-OFF Red Cap
456-102-10	1A (ON)-OFF Red Cap, Pkg/10
456-121	1A ON-(OFF) Black Cap
456-122	1A ON-(OFF) Red Cap

() = Momentary



MODEL	DESCRIPTION
SS201-1-BG	SPST 6A, ON-OFF, Screw terminals
SS202P-BG	SPST 20A, ON-OFF, Quick Connect Tabs
SS203P-BG	DPST 20A, ON-OFF, Quick Connect Tabs
SS205-5-BG	SPST 10A, ON-OFF, Wire leads
SS206-15-BG	SPDT 20A, ON-OFF-ON, Screw terminals
SS206R-BG	SPDT 20A, ON-ON, Screw terminals
SS206S-BG	SPST 20A, ON-OFF, Screw terminals
SS207-7A-BG	DPST 20A, ON-OFF, Screw terminals
SS208-16-BG	DPDT 20A, ON-OFF-ON, Screw terminals
SS208R-BG	DPDT 20A, ON-ON, Screw terminals
SS211-16A-BG	DPST 20A, ON-OFF, Screw terminals

Relays

GENERAL PURPOSE - 5A



467-120



General purpose 5A Relays. Relays can be soldered or inserted into sockets. Contacts rated 5A / 250VAC. Use sockets: R95-106A or R95-122

MODEL	DESCRIPTION
468-112	DPDT 12VDC
468-012	4PDT 12VDC
468-024	4PDT 24VDC
467-120	4PDT 120VAC

GENERAL PURPOSE - 10A

NTE

General purpose 10A relays, can be soldered or inserted into sockets. Contacts rated 10A / 120VAC. Use sockets: R95-111, R95-120 or R95-121



R14-11A10-120

MODEL	DESCRIPTION
R14-11D10-12	DPDT 12VDC
R14-11D10-24	DPDT 24VDC
R14-11A10-24	DPDT 24VAC
R14-11A10-120	DPDT 120VAC