

HDMI Splitters



HDMSP-1X2



HDMSP-1X4



HDMSP-1X8

Front



Back



HDMSP-1X16

HDMI SPLITTERS



- Supports HDMI resolution: 1080P, 1080i, 720P, 576P, 576i, 480P, 480i
- Supports deep colour 36 bit, with 3D for HDMI 1.4a
- Supports audio format: LPCM, Dolby AC3, DTS7.1, DSD

These HDMI splitters allow users to connect any digital video source with an HDMI output to multiple digital displays.

MODEL	OUTPUTS	DIMENSIONS (LXWXH)	
HDMSP-1X2	2	111 x 75 x 23.5mm	
HDMSP-1X4	4	111 x 75 x 23.5mm	
HDMSP-1X8	8	317 x 156 x 28mm	
HDMSP-1X16	16	419 x 200 x 44mm	

HDMI SPLITTER 1X2 W/ PIGTAIL

Unpowered cable adapter, one HDMI-A male to two HDMI-A female connectors; overall length 12".



MODEL	DESCRIPTION	
HDMSP-1X2P	HDMI Splitter 1x2 w/ Pigtail	

HDMI Extenders

CAT5E/6



Allows sending HDMI signals over long distances, with Send and Receive units and CAT5e or CAT6 cables, up to 50m in length. Cables sold separately.

MODEL	
HDMR-100A	

HDMI Wireless



HDMI WIRELESS EXTENDER

- Supports HDMI1.3 (1080P) and HDCP1.2
- Operating frequency: 5.1 to 5.9GHz
- Bandwidth: 40MHz

Achieve instant wireless transmission of HDMI signals up to 30m in an unobstructed indoor environment. Includes Send and Receive units, each one powered by a 5V adapter. Initial setup creates a point-to-point arrangement, expandable to point-to-multipoint or multipoint-to-multipoint.

MODEL	
HDMR-800	

HDMI Converters

COMPONENT/AUDIO



This HDMI converter allows component video devices to be integrated into digital A/V setups. This adapter also takes digital audio and encodes it onto the HDMI signal for the full HDMI effect.



MODEL	
HDMC-104	

VGA/AUDIO

Converts an analog source signal (VGA video + L-R RCA audio) to an HDMI signal for viewing on HD monitors. Maximum input resolution: 1280x1024 @ 60Hz. 5V DC adapter included.



MODEL	
HDMC-106	

MHL TO HDMI CONVERTER



Connect portable devices (smartphones, tablets, etc.) to HD TVs without signal loss.



MODEL	
214-7140	