
































**AC/DC Switching Power Supplies**

Compact and lightweight enclosed switching power supplies. Overload, over-voltage and short circuit protection. Voltage regulation at full load within 0.5%. Screw terminal input and output.

MODEL	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	DIMENSIONS	APPROVAL
<b>25 WATT</b>					
PSF25-5	85 -264VAC or 120 - 370VDC	5VDC	5A	99 x 82 x 35mm	c  US
PSF25-12	85 -264VAC or 120 - 370VDC	12VDC	2.1A	99 x 82 x 35mm	c  US
PSF25-15	85 -264VAC or 120 - 370VDC	15VDC	1.7A	99 x 82 x 35mm	c  US
PSF25-24	85 -264VAC or 120 - 370VDC	24VDC	1.1A	99 x 82 x 35mm	c  US
<b>60 WATT</b>					
PSF60-5	85-264VAC or 120-370VDC	5VDC	12A	160 x 98 x 39mm	c  US
PSF60-12	85-264VAC or 120-370VDC	12VDC	5A	160 x 98 x 39mm	c  US
PSF60-15	85-264VAC or 120-370VDC	15VDC	4A	160 x 98 x 39mm	c  US
PSF60-24	85-264VAC or 120-370VDC	24VDC	2.5A	160 x 98 x 39mm	c  US
PSF60-48	85-264VAC or 120-370VDC	48VDC	1.3A	160 x 98 x 39mm	c  US
<b>100 WATT</b>					
PSF100-5	85-264VAC	5VDC	20A	199 x 98 x 39mm	c  US
PSF100-7.5	85-264VAC	7.5VDC	13.5A	199 x 98 x 39mm	c  US
PSF100-12	85-264VAC	12VDC	8.5A	199 x 98 x 39mm	c  US
PSF100-15	85-264VAC	15VDC	6.7A	199 x 98 x 39mm	c  US
PSF100-24	85-264VAC	24VDC	4.5A	199 x 98 x 39mm	c  US
PSF100-48	85-264VAC	48VDC	2.2A	199 x 98 x 39mm	c  US
<b>120 WATT</b>					
ESP-120-13.5	88-132 or 176-264VAC	13.5VDC	8A	150 x 140 x 80mm	
<b>150 WATT</b>					
PSF150-5	88-132 or 170-264VAC	5VDC	30A	199 x 110 x 50mm	c  US
PSF150-7.5	88-132 or 170-264VAC	7.5VDC	20A	199 x 110 x 50mm	c  US
PSF150-9	88-132 or 170-264VAC	9VDC	17A	199 x 110 x 50mm	c  US
PSF150-12	88-132 or 170-264VAC	12VDC	12.5A	199 x 110 x 50mm	c  US
S-150-15	88-264VAC; 248-370VDC	15V	10A	199 x 110 x 50mm	c  US
PSF150-24	88-132 or 170-264VAC	24VDC	6.5A	199 x 110 x 50mm	c  US
S-150-48	88-264VAC; 248-370VDC	48VDC	3.2A	199 x 110 x 50mm	c  US
<b>240 WATT</b>					
PSF240-12	85-132 or 170-264VAC	12VDC	18A	199 x 110 x 50mm	c  US
PSF240-24	85-132 or 170-264VAC	24VDC	10A	199 x 110 x 50mm	c  US
S-240-48	88-264 VAC or 248-370VDC	48VDC	5A	190 x 93 x 63mm	c  US
<b>320 WATT</b>					
PSF320-12PF	85-264VAC, 120-370VDC	12VDC	25A	215 x 115 x 50mm	c  US
PSF320-24PF	85-264VAC, 120-370VDC	24VDC	13.0A	215 x 115 x 50mm	c  US
<b>600 WATT</b>					
SE-600-12	90-132 or 180-264 VAC	12VDC	50A	247 x 127 x 64mm	c  US
SE-600-24	90-132 or 180-264 VAC	24VDC	25A	247 x 127 x 64mm	c  US
SE-600-48	90-132 or 180-264 VAC	48VDC	12.5A	247 x 127 x 64mm	c  US



**PSF SERIES: CIRCUIT-TEST**

Enclosed switching power supply with aluminum chassis and vented metal cover.



**S-150 SERIES:**

Enclosed switching power supply with metal chassis and vented metal cover.



**S-240, SE-600 SERIES:**

Enclosed switching power supply with metal chassis.

