

DC Fans

Manufactured with high quality industry standards Circuit-Test fans deliver high performance, efficiency and reliability. Made with Glass fibre reinforced plastic or Die cast aluminum the DC Brushless fans are available in wide range of sizes to fit most applications. These industrial quality cooling fans are ideal for Data communications, Instrumentation and many other computer and electronic applications. Available in 5, 12 and 24VDC, these fans have 3 wire leads and offer the "locked rotor alarm sensor" as a standard feature. They also meet the North American safety standard approvals CSA/UL. Frame: Glass fibre reinforced plastic 94V-0 PBT or Die Cast aluminum.

- Impeller: Glass fibre reinforced plastic 94V-0 PBT
- Bearing: Ball or Sleeve
- Input Voltage: 5, 12 or 24VDC
- Connection: 3 Wire leads
- Approvals: CSA/UL

CIRCUIT-TEST 

OEM pricing available



MODEL	DIMENSIONS	AIR FLOW	CONNECTION	BEARINGS	IMPELLER	
5VDC						
CFA054010HB	40 x 40 x 10mm (1.57 x 1.57 x 0.39")	7.7 CFM	Wire Leads	Ball	Plastic	
12VDC						
CFA124010MB	40 x 40 x 10mm (1.57 x 1.57 x 0.39")	6.5 CFM	Wire Leads	Ball	Plastic	
CFA124010MS	40 x 40 x 10mm (1.57 x 1.57 x 0.39")	6.5 CFM	Wire Leads	Sleeve	Plastic	
CFA124020MB	40 x 40 x 20mm (1.57 x 1.57 x 0.79")	7 CFM	Wire Leads	Ball	Plastic	
CFA124020MS	40 x 40 x 20mm (1.57 x 1.57 x 0.79")	7 CFM	Wire Leads	Sleeve	Plastic	
CFA124020HS	40 x 40 x 20mm (1.57 x 1.57 x 0.79")	8.5 CFM	Wire Leads	Sleeve	Plastic	
CFA125010MS	50 x 50 x 10mm (1.97 x 1.97 x 0.39")	8.8 CFM	Wire Leads	Sleeve	Plastic	
CFA125010HS	50 x 50 x 10mm (1.97 x 1.97 x 0.39")	12.2 CFM	Wire Leads	Sleeve	Plastic	
CFA126015MS	60 x 60 x 15mm (2.36 x 2.36 x 0.59")	20 CFM	Wire Leads	Sleeve	Plastic	
CFA126025MB	60 x 60 x 25mm (2.36 x 2.36 x 1")	16.7 CFM	Wire Leads	Ball	Plastic	
CFA126025MS	60 x 60 x 25mm (2.36 x 2.36 x 1")	16.7 CFM	Wire Leads	Sleeve	Plastic	
CFA128015HS	80 x 80 x 15mm (3.15 x 3.15 x 0.59")	39 CFM	Wire Leads	Sleeve	Plastic	
CFA128025LS	80 x 80 x 25mm (3.15 x 3.15 x 1")	30 CFM	Wire Leads	Sleeve	Plastic	
CFA128025MB	80 x 80 x 25mm (3.15 x 3.15 x 1")	37 CFM	Wire Leads	Ball	Plastic	
CFA128025MS	80 x 80 x 25mm (3.15 x 3.15 x 1")	37 CFM	Wire Leads	Sleeve	Plastic	
CFA129225LS	92 x 92 x 25mm (3.62 x 3.62 x 1")	41.5 CFM	Wire Leads	Sleeve	Plastic	
CFA129225MB	92 x 92 x 25mm (3.62 x 3.62 x 1")	50 CFM	Wire Leads	Ball	Plastic	
CFA129225MS	92 x 92 x 25mm (3.62 x 3.62 x 1")	50 CFM	Wire Leads	Sleeve	Plastic	
CFA1212038MB	119 x 119 x 38mm (4.7 x 4.7 x 1.5")	121 CFM	Wire Leads	Ball	Plastic	
CFA1212038MS	119 x 119 x 38mm (4.7 x 4.7 x 1.5")	121 CFM	Wire Leads	Sleeve	Plastic	
CFA1212025LS	120 x 120 x 25mm (4.7 x 4.7 x 1")	61 CFM	Wire Leads	Sleeve	Plastic	
CFA1212025MB	120 x 120 x 25mm (4.7 x 4.7 x 1")	74 CFM	Wire Leads	Ball	Plastic	
CFA1212025MS	120 x 120 x 25mm (4.7 x 4.7 x 1")	74 CFM	Wire Leads	Sleeve	Plastic	
24VDC						
CFA244020MS	40 x 40 x 20mm (1.57 x 1.57 x 0.79")	7 CFM	Wire Leads	Ball	Plastic	
CFA246025MS	60 x 60 x 25mm (2.36 x 2.36 x 1")	17 CFM	Wire Leads	Ball	Plastic	
CFA248025MS	80 x 80 x 25mm (3.15 x 3.15 x 1")	37 CFM	Wire Leads	Ball	Plastic	
CFA249225MS	92 x 92 x 25mm (3.62 x 3.62 x 1")	50 CFM	Wire Leads	Ball	Plastic	
CFA2412038MS	119 x 119 x 38mm (4.7 x 4.7 x 1.5")	121 CFM	Wire Leads	Ball	Plastic	
CFA2412025MS	120 x 120 x 25mm (4.7 x 4.7 x 1")	74.5 CFM	Wire Leads	Ball	Plastic	