

CIRCUIT-TEST

Single Output Power Supplies - 150 Watt Series



- AC input range selected by switch
- High reliability
- Approvals: UL, CE
- Protections: overload/ over voltage/ short circuit
- 2 years warranty
- F615UL 199 x 110 x 50(mm)

SPECIFICATIONS

AC input voltage range	88~132 / 170~264VAC selected by switch
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Output voltage adjust range	± 10%
Output overload protection	110~130%
Output over voltage protection	115~150%
Withstand voltage	I/P-O/P: 3.0KVAC/1min, I/P-F/G: 1.5KVAC/1min, O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10°C~ +50°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~ +85°C, 20%~95%RH (non condensing)
Safety standards	GB4943, UL60950, EN60950
EMC standards	GB9254, EN55022 classB, EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		Load Regul.	R&N	Efficiency
PSF150-5	5V	30A	0.5%	120mV	78%
PSF150-7.5	7.5V	20A	0.5%	120mV	80%
PSF150-9	9V	16.7A	0.5%	120mV	80%
PSF150-12	12V	12.5A	0.5%	120mV	82%
PSF150-24	24V	6.5A	0.5%	150mV	85%
PSF150-27*	27V	5.6A	0.5%	150mV	85%
PSF150-36*	36V	4.2A	0.5%	200mV	86%

* Special Order

CIRCUIT-TEST

Single Output Power Supplies - 150 Watt Series

F615UL

